1. Introduction:

86 18 is a whole new generation of single door controller with swipe card, card with password and password operation. It makes use of mobile technology mode button with blue LED backlight. Functions developed for the latest microprocessor with high stability, large capacity, reaction speed and simple operation. This is the best choice for companies, factories, residences, offices, mechanical and electrical control rooms.

2. Functions:

1) Support up to 2000 cards (ID/IC selectable)
2) Cards registration can be continuous and controller will generate default card number and card password automatically.
3) Have the door open and close by card functions.

1) Cards to the door open and close by card functions.

4)Output signal directly from the open relay for door open function (NO/NC selectable)
5)Supports 4 modes of door open methods:Card only, Password only, Card or Password and Card And Password

Card or Password and Card And Password 3. Technical Features:

9	∞	7	6	5	4	w	2	-	No.
Car type	Induction distance	Memory capacity	RH	Ambient temp.	Weight	Dimension	Max load	Power supply	Item
EM or MEI	5-15CM	Information of 2000 user card, and 1 passwords	20%80%	-10°C50°C	150g	86mm×86mm×20mm	Alarm output: 100mA Electrolock output: 5A	DC: Voltage 12V ± 10%; current < 0.1A	Specification

Invalid Entry

Alarm Mode

Di Di Di Continuously Di (long) Di (long)

4. Technical Features:

Setup Failure	Setup Failure	Setup Successfully	Button tone	Password Only Mode Flash for each second	Card and Password Mode Flash for each 0.5 second	Card and Password Mode (after swipe card, pending Red ar for password entry)	Card Only Mode	Non registered Card	Under Program Mode	Program Mode	Normal Mode	Description Rec
				or each	or each cond	Red and Green LED blink interactively	ON with same duration of door open	ON	ON	Flash	ON	Ked LED Green LED
(Di (long)	Di Di (short)	Di (short)			actively	oor open Di Di (short)	Di (long)		r		Buzzer